


Female Header Pitch:2.00mm
Dual Row/Side Entry / Straight DIP Type

Series
47B 20

Odia 奥比亚

Tel: (+86)0755-28248661/2/3
Fax: (+86)0755-27857873






SPECIFICATIONS (技术参数):

Current Rating (额定电流): 2.0 AMP
Contact Resistance (接触电阻): 30mΩ Max
Insulation Resistance (绝缘电阻): 1000MΩ Min
Withstand Voltage (耐压值): 500VAC/minute
Operation Temperature (工作温度): -40℃ to +105℃

MATERIALS (材质):

Contact Material (接触件材质): Phosphor Bronze
Contact Plating (接触件电镀): Gold or Tin over 50 μ "Ni
Insulator Material (绝缘体材质): Polyester(UL94V-0)
Standard: PA66



PCB LAYOUT

Ordering Code

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩
47B 20 9 2 18 S 1 4 1 0

① Series No.:
47B = Female Header

③ Insulator Height:
9 = 4.9mm

② Pitch: 20 = 2.00mm

④ Number of row:
1=Sing row
2=Double row

⑤ Number of Contacts:
Single row=01(1x1)to 40(1x40)
Double row=04(2x2)to 80(2x40)

⑥ Tail & Mounting Style:
S=Straight DIP type

⑦ Contact Plated
0=Tin
1=Gold Flash
2=Gold 3u"
3=Gold 5u"
4=Gold 10u"
5=Gold 15u"
6=Gold 30u"
A=Gold 1.5u"
B=Gold 2u"

⑧ Material Type
0=PPS
1=PBT
2=LCP
3=Nylon-9T
4=Nylon-6T
5=PA46

⑨ Color: 1=Black

⑩ Customer Request