



NOTE:

1.MATERIAL:

- a.HOUSING:PBT UL94V-0
- b.CONTACT:BRASS
- (SURFACE PLATING: Sn100u"-120u")
- SEE ORDERING INFORMATION

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -25°C~ +85°C

PCB Layout Diagram  
Top View

客户品名				Units		mm	Scale	2:1	Drawing By		Date		<b>Odia</b> ® 广东澳迪亚电子有限公司 <a href="http://www.odiachina.com">HTTP://WWW.ODIACHINA.COM</a>	
客户料号				Tolerance Unless Otherwise Specified				Reviewed By		Date		Date		
E				X.X ~ ±0.25				Date		Title		BS-2CR2032-7DIP4		
D				X.XX ~ ±0.20				Date		Sheet		1 of 1		
C				X.XXX ~ ±0.10				Date		Third Angle Projection		Drawing No.		
B				Angle ~ ±0.50°				Date				F/Name		
A	RELEASED			2020/5/10				Date				REV		
REV	ECN.NO.			Date				Date				A		