



NOTE:

1.MATERIAL:

a.HOUSING:PA66

b.CONTACT:PHOSPHOR BRONZE
(SURFACE PLATING: Sn 100u"-120u")
SEE ORDERING INFORMATION

2.ELECTRIC:

a.CONTACT RESISTANCE: 30 MILLIOHMS MAX

b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN

c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL

d.OPERATING TEMPERATURE: -25°C~ +85°C

PCB Layout Diagram
Top View

客户品名	
客户料号	
E	
D	
C	
B	
A	RELEASED
REV	ECN.NO.

Units	mm	Scale	2:1	Drawing By	Date
Tolerance Unless Otherwise Specified				Reviewed By	Date
X.X ~ ±0.25				Approvai By	Date
X.XX ~ ±0.20					
X.XXX ~ ±0.10					
Angle ~ ±0.50°					

Odia ® 广东澳迪亚电子有限公司		HTTP://WWW.ODIACHINA.COM	
Date	2020/5/10	Title	BS-2430-2SnDIP
Sheet	1 of 1		
Third Angle Projection		Drawing No.	REV
		F/Name	A